

Method Summary: Test Method SR-95

Rapid Determination of Radiostrontium Using Empore[™] Strontium RAD Disks

Product Description

Empore[™] Strontium RAD Disks provide an efficient alternative to conventional radiochemical sample preparation methods that use wet chemistry or packed columns. A proprietary process is used to entrap radium selective adsorbent particles into a matrix of inert PTFE to create a mechanically stable sorbent disk. The disks can be used for purification and concentration of radium from aqueous samples.

Emporestrontium RAD disks provide a sample prep solution for large volume aqueous samples and the disk format provides a large surface area for sorbent/ sample contact.

Scope and Application

This method is intended for determination of radioactive Strontium in aqueous samples. Using Emporestrontium RAD disks, sample processing and counting source preparation may be condensed into a single step. This preparation takes approximately 20 min. for a one liter sample and is amenable to batch processing. Total Sr content should not exceed 3 mg to obtain quantitative recovery. For typical one liter samples, Sr retention is greater than 97%. The method detection limit depends on sample volume and counting protocol but generally will be less than 1 pCi/L.

Method Overview

An acidified sample is passed through an Empore strontium RAD disk to quantitatively extract the radiostrontium. The disk is then counted for beta activity.

Safety

When using solvents or other chemicals, be sure to read and follow the manufacturer's precautions, directions for use and disposal procedures.

Apparatus and Materials

- 47 mm Empore Strontium RAD Disks
- 47 mm single or multiple station vacuum manifold
- Beta detector proportional counter or liquid scintillation counter
- 50 mm planchets or scintillation vials

Reagents

- Nitric acid, concentrated and 2M
- Methanol
- Ammonium Hydroxide (optional)
- Acetone (optional)
- Scintillation cocktail (optional)

Sample Collection, Preservation, and Handling

Acidify the sample to 3 M with concentrated nitric acid. If visible solids are present in the sample, prefilter through a $0.45\mu m$ filter if exclusion is desired.

Empore Strontium RAD Disk Utilization

Proper disk utilization is critical for successful extraction and counting.

- 1. Mount an Empore strontium RAD disk in the vacuum manifold.
- 2. Condition the disk by covering it with 5 mL methanol and then slowly drawing the methanol through the disk with a gentle vacuum. Do not allow the disk to dry.



- 3. Wash the disk immediately with 20 mL of 2M nitric acid at a flow rate of approximately 50 mL/min.
- Treat the sample by pulling it through the disk at an approximate flow rate of 50 4 mL/min.
- 5. Rinse with 20 mL of 2M nitric acid (at approximately 50 mL/min). The end time of this rinse is recorded at the start of the ⁹⁰Y ingrowth.

Note: The disk should not be allowed to completely dry during the preconditioning and sample processing steps.

Excessive air should not be drawn through the membrane since airborne radon decay products

could pose radiometric interferences if the disks are counted the same day.

Counting Options

Disks may be counted by either proportional or scintillation counting. The instrument type, counting times and frequency of counts are dictated by the isotope(s) of interest and the data quality objectives. Radioactive ingrowth and decay corrections must be applied.

For use with a proportional counter, the disk must be dry and free of acid. Dry with acetone or in an oven.

For use with a scintillation counter, place disk (before disk dries) into a vial containing scintillation cocktail.

For full details on test procedure and possible interferences, consult test method "Rapid Determination of Radiostrontium using Empore Strontium RAD Disks".

Reference

S. C. Goheen, editor, DOE Methods for Evaluating Environmental and Waste Management Samples. Battelle Press, Columbus, OH (1997). Method RP515, Rapid determination of radiostron tium using Empore[™] Strontium RAD Disks.

Note: Empore Solid Phase Extraction Products are intended for solid phase extraction during scientific research only. These products

are not intended for use in medical devices or in assessment and

Important Notice

CDS Analytical MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUTNOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Since a variety of factors can affect the use and performance of a CDS Analytical product in a particular application, some of which are uniquely within the user's knowledge and control, user is responsible for determining whether or not the CDS Analytical product is fit for a particular purpose and suitable for user's method of application.

Warranty

Seller warrants its equipment against defects in workmanship and material for a period of 12 months from date of shipment from the factory under normal use and service and otherwise when such equipment is used in accordance with

instructions furnished by Seller and for purposes disclosed in writing at the time of purchase, if any. Any unauthorized alteration of modification of the equipment by Buyer will void this warranty. Seller's liability under this warranty shall be limited to the replacement or repair, F.O.B., point of manufacture, of any defective equipment or part which, having been returned to the factory, transportation charges prepaid, has been inspected and determined by Seller to be defective. THISWARRANTY

ISINLIEUOFANYOTHERWARRANTY, EITHEREXPRESSEDORIMPLIED, ASTO DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR USE, OR ANY OTHER MATTER. Under no circumstances shall Seller be liable to Buyer or any third party for any loss of profits or other direct or indirect costs, expenses, losses or consequential damages arising out of or as a result of any defects in or failure of its products or any part or parts thereof or arising out of or as a result of parts or components incorporated in Seller's equipment but not supplied by the Seller.

Technical Information and Data

Technical information and data, recommendations, and other statements provided by CDS Analyticalarebasedoninformation,tests,orexperiencewhichCDS Analytical believes to be reliable, but the accuracy or completeness of such information is not guaranteed. Such technical information and data are intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any CDS Analytical or third party intellectual property rights is granted or implied with this information.

Safety and Disposal

Always follow safe handling practices while processing Empore products as applicable to your use. Always wear appropriate personal protective equipment while processing Empore products as applicable to your use. Dispose of used Empore products per requirements of your process. Alteration or addition of other materials to Empore products may require unique disposal protocols. Always dispose of used product in accordance with federal, state and local requirements.

Safety Information

`WARNING:	result in death or serious injury.
	WARNING:
Toreduce the risks a radiochemical ma • Read, understand Instructions for	ssociated with environmental contamination, handling terials or false negative results: I and follow all recommendations in the product MSDS and Use.
 To reduce the risks associated with radiochemical materials: Always wear the proper PPE (Personal Protection Equipment) when handling used product. 	
 Dispose of used d 	ks associated with environmental contamination:

regulations. Unused disks may be disposed of in accordance with standard procedure for laboratory waste.



treatment of clinical patients.

465 Limestone Rd, Oxford, PA 19363 Toll Free: 1-800-541-6593

Empore is a trademark of CDS Analytical. Used under license. © CDS Analytical LLC 2018. All Rights Reserved. Printed in the USA. GN-18 10/23 5k